

RWX300 (H580)

Informasjon

Maks løft: 3000kg

Egenvekt: 6000kg

Standard steinskuffe: 1200liter

Ekstra uttak 63 l/m 235 bar

Maks fart: 35km/t

Høyde: 280cm

100 hk, 4,3l motor m. turbo

Hjulstandard 16/70-20

Hurtigkobling: hydraulisk

3 hydraulisk funksjon for ekstra uttak

God benplass, og mye mer



Frakkagjerdvegen 127
5563 FØRRESFJORDEN
Tlf: 52 77 0111
jan.bakken@wee.no

wee.no

H580

Engine

Max speed 2400rpm	H580
Power	76kW (103hp)
ISO 9242	74kW (96hp)
80/1269/EEC	74kW (96hp)
Diameter	102mm
Stroke	115mm
Displacement	4.3L

Hydraulic system

	H580
Main valve pressure	235bar
Displacement	63L/min
Hydraulic cycle time	
Lift	5secs
Down	4secs
Dump	2secs
Tilt	2.5secs



Driving speed

	H580
1st gear	5km/h
2nd gear	11km/h
3rd gear	16km/h
4th gear	28km/h

Volume

	H580
Fuel	50L
Hydraulic	40L
Engine oil	110L



Operation

Model		H580	
Quick hitch		HP	SSL
Tire	m	16/70-20	
Self weight	kg	5570	5620
Bucket capacity	m	1.2	1.2
Break power(kg/m)	kN	56	46
Lifting capacity (mm)	kg	3000	3000
Straight static load	kg	5100	4775
35 degree load	kg	3650	3410